



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant : Michael SCHITZKUS et al
Based on : 10305310.7 filed on February 10, 2003
For : Device For Damping Pressure Pulsations

Docket No. : R. 304680

Customer No. : 02119

Date: July 2, 2004

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

**INFORMATION DISCLOSURE STATEMENT UNDER 37 CFR 1.97(b),
AND EXPLANATION OF THE RELEVANCE OF THE CITED PRIOR ART**

Sir:

The undersigned hereby requests that the prior art cited on the attached prior art statement be placed of record in the application file.

This citation of prior art is made under 37 CFR 1.97(b), since it is being filed within three months of the filing of this application, and before receipt of the first Office action.

The relevance of the prior art cited on the attached form 1449 is as follows:

DE 100 16 895

According to the disclosure of this patent, the hydraulic block (1) includes a piston(18) which is movable in relation to the wall of a cylindrical opening of an accumulator. The aforesaid wall is formed by the wall of a bore (14) in the hydraulic block. The cover (20) closing off the accumulator is inseparably connected to the hydraulic block, preferably by caulking or clinching. The cover and/or piston are formed cup-shaped from sheet metal or plastic, and at least the piston on its side wall has an encircling groove for a seal (21).

DE 42 34 013

In this patent, valve elements (1, 1') are arranged in several valve reception bores of the housing block (3). The bores are arranged in two rows. Several pressure medium bores (4), connecting the valve elements to each other, are arranged between the two diametrically aligned valve rows (x, y). Reception bores (7, 8) having the pressure generating element (5) and the drive element (6) are provided. Further reception bores aligned axis parallel to each other, open out in to the valve reception body (3) are provided. The reception bore (7) with the pressure generating element (5) is arranged in parallel with the two rows of valves.


DE 41 11 201

According to the teachings of this patent, a hydraulic regulator is inserted in the brake line (4) between the master braking cylinder (1), coupled to the brake pedal (2) and a wheel braking cylinder (5). It incorporates a valve (20) providing the

anti-locking braking regulation, and a damping chamber (8) communicating with the brake line (4) between the master braking cylinder (1) and the valve (20). The damping chamber (8) is provided by a blind bore (9) in a housing block (7), receiving a throttle insert (11), which is held in place by the valve (20) fitted to the housing block (7).

Examination of this application is respectfully requested.

Respectfully submitted,



Ronald E. Greigg
Registration No. 31,517
Attorney for Applicants

GREIGG & GREIGG, PLLC
1423 Powhatan Street, Suite One
Alexandria, VA 22314

Telephone: 703-838-5500
Facsimile: 703-838-5554

REG/SLS/nc
Customer No. 02119

Date: July 2, 2004

J:\Bosch\R304680\04-05-18, R304680, IDS before 1st OA.wpd

INFORMATION DISCLOSURE CITATION
(Use several sheets if necessary)



Docket Number (Optional) R.304680	Application Number
Applicant(s) Michael SCHLITZKUS et al	
Filing Date	Group Art Unit

U.S. PATENT DOCUMENTS

EXAMINER INITIAL	REF	DOCUMENT NUMBER	DATE	NAME	CLASS	SUBCLASS	FILING DATE IF APPROPRIATE

FOREIGN PATENT DOCUMENTS

	REF	DOCUMENT NUMBER	DATE	COUNTRY	CLASS	SUBCLASS	Translation	
							YES	NO
		DE 100 16 895	18 Oct. 01	Germany				✓
		DE 42 34 013	14 Apr. 94	Germany				✓
		DE 41 11 201	08 Oct. 92	Germany				✓

OTHER DOCUMENTS (Including Author, Title, Date, Pertinent Pages, Etc.)

EXAMINER	DATE CONSIDERED
----------	-----------------

EXAMINER: Initial if citation considered, whether or not citation is in conformance with MPEP Section 609; Draw line through citation if not in conformance and not considered. Include copy of this form with next communication to applicant.